

Dromex



CHEMICAL NITRILE GLOVE



0056

Description

Dromex® 0056, green flock lined Nitrile gloves protects the hands against many solvents and oil-based chemicals, whilst providing protection against abrasion, cuts, snags and punctures.

Impermeable to chemicals and microorganisms, features a raised pattern on palm, fingers and partially on the wrist for grip, with a curved finger design helps reduce hand fatigue.


Suitable for use when handling chemicals in labs, cleaning, janitorial applications and environmental clean-up. Used in industries such as chemical processing, oil refining petrochemicals, food processing, automotive assembly, painting and maintenance.

Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

EN 388: 2003



3101

EN 374: 2003



KLJ

EN 374: 2003



Compliance & Conformity

Complies with the requirements of CE type examinations EN 420 for innocuousness EN 388:2003, (3,1,0,1) for mechanical risks, EN 374 - 2:2003 and EN 374 - 3:2003, protective gloves against dangerous chemicals and micro-organism for compliance with directive 89/686/EEC.

Specifications

Style: Wing thumb, flock lined, with anti-slip patterned palm, finger and partial wrist
Nitrile
Liner:
Palm: 0.38 mm $\pm$ 5 %
Back: 0.38 mm $\pm$ 5 %
Cuff: 12cm open wrist cuff with pattern for ease of glove removal
Mass: 76g Per pair (size 11)

CAT III

EN 374-3 : 2003			
Name of Chemicals	Sulfuric Acid 96%	Sodium Hydroxide 40%	n-Heptane
Letter code of the product	L	K	J
Permeation Performance Levels	3	6	6

Packaging, Storage & Obsolescence

Packed 12 pairs per bundle and 120 pairs per carton for shipping. Store in a cool, dry, dark place. Stored correctly, the gloves physical properties will not change for up to three years.




Cleaning & Maintenance

Gloves should not be left in a contaminated condition, if re-use is intended especially if potential hazards exist. Before removal from the hands, excess contaminant should first be removed from the gloves.

Should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands.

The gloves may then be decontaminated as indicated below.



We recommend that no bleaching or oxidising ingredients or any fabric softeners be used.

Recommended washing temperature is 30°C with mild detergents.

Clean with warm water and soap.

Wipe with a clean cloth and hang in a ventilated area to dry naturally.

Keep away from any direct fire or source of heat.

There is no remarkable impact on cut resistance during the normal life-cycle of a glove, however depending on glove construction, staining and cleaning method the differences in shrinkage and colour may occur.

In order to maximise the glove life cycle, we recommend the mildest possible cleaning conditions in terms of temperature, chemicals and cycle duration.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.

Sizes Available

6-10

Code	Size	Palm Length
0056-6	XXS	95mm ($\pm$ 2mm)
0056-7	XS/S	100mm ($\pm$ 2mm)
0056-8	S/M	113mm ($\pm$ 2mm)
0056-9	M/L	125mm ($\pm$ 2mm)
0056-10	L/XL	130mm ($\pm$ 2mm)


* As per the EN420 standard, actual measurement of gloves are determined by the manufacturer, taking into account the behaviour of the glove material, its thickness (such as leather gloves, PVC gloves etc), elasticity and the intended use.

* Sizing charts only serve as a guide. Sizes and measurements are for reference only. In order to make an informed decision, always try on the gloves as each glove features a unique construction to accommodate a wearer's preferences.

Marking



Measurement Guide



Materials



1. Wing thumb
2. Raised palm & finger pattern
3. Open cuff

Dromex: Cornubia Ridge Logistics Park, 30 Umganu Road,
Flanders, Blackburn, Durban, South Africa, 4319
T. +27(31) 713 1960 E. info@dromex.co.za www.dromex.co.za

Disclaimer

Dromex reserves the right to make changes without further notice to any products herein to improve function, design or reliability and validity. Dromex does not assume any liability arising out of the application or use of any product described herein. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

Latest update: 04/03/2025